Material Safety Data Sheet

PURESPRAY GREEN SPRAY OIL 13E



1. Product and company identification

Product name : PURESPRAY GREEN SPRAY OIL 13E

Code : PSGCAN, 440-198-1

Material uses : Purespray Green Spray Oil 13E is a PMRA registered emulsifiable horticultural spray oil.

Pest Control Products Act Registration Number: 27666

Manufacturer : Petro-Canada Lubricants Inc., a Suncor Energy Business

2310 Lakeshore Road West

Mississauga, Ontario Canada L5J 1K2

In case of emergency : Suncor Energy: 403-296-3000

Canutec Transportation: 613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

2. Hazards identification

Physical state : Viscous liquid.

Odour : No odour or slight petroleum oil like.

WHMIS (Canada) : Not controlled under WHMIS (Canada).

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and

available for employees and other users of this product.

Emergency overview: No specific hazard.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

Potential chronic health effects

Chronic effects
 No known significant effects or critical hazards.
 Carcinogenicity
 Not listed as carcinogenic by OSHA, NTP or IARC.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Powelopmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Medical conditions
aggravated by over
: No known significant effects or critic
: Repeated or prolonged contact with
severe skin irritation. Repeated skin

exposure de

Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated skin exposure can produce local skin destruction or dermatitis.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name
Mixture of severely hydrotreated and hydrocracked base oil (petroleum).

CAS number
Mixture

Mixture
-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds Page: 1/7

Petro-Canada is a Suncor Energy business

Page Number: 2

4 First-aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 Fire-fighting measures

Flammability of the product

: May be combustible at high temperature.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Products of combustion

: Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing

Special protective equipment for fire-fighters

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

: Low fire hazard. This material must be heated before ignition will occur.

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Accidental release measures 6.

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds Page: 2/7

Petro-Canada is a Suncor Energy business

Page Number: 3

6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits
Mixture of severely hydrotreated and hydrocracked base oil (petroleum).	ACGIH TLV (United States). Notes: (Mineral oil) TWA: 5 mg/m³, (Inhalable fraction) 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour filter

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommended: neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds Page: 3/7

Petro-Canada is a Suncor Energy business

Exposure controls/personal protection 8.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties 9

Physical state : Viscous liquid.

Flash point Open cup: 174°C (345.2°F) [Cleveland.]

Auto-ignition temperature Not available. Flammable limits Not available.

Colour Colourless to light yellow.

Odour No odour or slight petroleum oil like.

Not available. **Odour threshold** Not available. pН **Boiling/condensation point** : Not available. **Melting/freezing point** Not available.

: 0.855 kg/L @ 15°C (59°F) Relative density

Vapour pressure Not available. Vapour density Not available. Not available. **Volatility Evaporation rate** Not available.

Viscosity 13.6 cSt @ 40°C (104°F), 3.18 cSt @ 100°C (212°F)

Pour point Not available.

Solubility Insoluble in water. Easily dispersed in water.

10. Stability and reactivity

Chemical stability

: The product is stable.

Hazardous polymerisation

Under normal conditions of storage and use, hazardous polymerisation will not occur.

Materials to avoid

Reactive with oxidising agents.

Hazardous decomposition

products

: May release COx, smoke and irritating vapours when heated to decomposition.

Toxicological information

Acute toxicity

Product/ingredient name **Species** Result **Dose Exposure** Mixture of severely hydrotreated and LD50 Dermal Rabbit >2000 mg/kg

hydrocracked base oil (petroleum).

LD50 Oral Rat >5000 mg/kg

4 hours LC50 Inhalation Rat >5.2 mg/L

Dusts and mists

Conclusion/Summary

Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitiser

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds Page: 4/7

Petro-Canada is a Suncor Energy business

PURESPRAY GREEN SPRAY OIL 13E Page Number: 5

11. Toxicological information

Conclusion/Summary

: Not available.

A4

Carcinogenicity

Conclusion/Summary: Not available.

Classification

Product/ingredient name ACGIH IARC EPA NIOSH NTP OSHA

Mixture of severely hydrotreated and

hydrocracked base oil (petroleum).

Mutagenicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

12. Ecological information

Environmental effects

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Conclusion/Summary :

: Not available.

Biodegradability

Conclusion/Summary: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	 Additional information
TDG Classification	Not regulated.	-	-	-	-
DOT Classification	Not available.	Not available.	Not available.	-	-

PG*: Packing group

15. Regulatory information

United States

HCS Classification : Not regulated.

Canada

WHMIS (Canada)
: Not controlled under WHMIS (Canada).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

Canada inventory : All components are listed or exempted.
United States inventory : All components are listed or exempted.

(TSCA 8b)

Europe inventory : All components are listed or exempted.

International lists

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

16. Other information

Hazardous Material Information System (U.S.A.)

Health1Flammability1Physical hazards0Personal protectionB

National Fire Protection Association (U.S.A.)



References: Available upon request.

™ Trademark of Suncor Energy Inc. Used under licence.

Date of printing : 9/2/2011.

Date of issue : 24 August 2011

Date of previous issue : 8/25/2010.

Responsible name : Product Safety - RS

Indicates information that has changed from previously issued version.

For Copy of (M)SDS

: The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: lubricants.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds

Page: 6/7

PURESPRAY GREEN SPRAY OIL 13E

Page Number: 7

16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue: 8/24/2011. Internet: lubricants.petro-canada.ca/msds Page: 7/7